

COLORS



FINISHING



FEATURES

















- High Performances: A L C airflow level control to manage the temperature on shelves (three regulations)
- Visibility: extraordinary enhancement of displayed
- Practicality: pistons assisted front glass opening system
- Customizable: great possibility to customize front side
- Energy Saving: double LED lighting as standard



MYA COLLECTION: CIAM's spearhead production. It is the perfect synthesis of PERFORMANCE, ERGONOMICS, ENERGY SAVING, DISPLAYED PRODUCT VISIBILITY. High performance maintains the product even in the worst ambient condition. You will be surprised by MYA's performance. MYA cabinets are tested in class 4+ (35°C / 70% HR): even in the worst ambient condition, MYA cabinets can ensure a perfect food preservation. Maximum flexibility: A.L.C airflow level control to manage the temperature on the shelves (three different set points). All the upper glass structure of MYA's cabinets is realized in double glazing, to avoid the fog even in high relative humidity conditions.










TECHNICAL FEATURE		VERSIONS			
		1150	1650	2150	45° Open Corner
External dimensions (L-D-H)	inches mm	46 ¼"- 48 ¾"- 54 ⅓" 1175 - 1237 - 1380	65 ½''- 48 ¾"- 54 ⅓" 1675 - 1237 - 1380	85 ² / ₃ "- 48 ³ / ₄ "- 54 ¹ / ₃ " 2175 - 1237 - 1380	85 ² / ₃ "- 48 ³ / ₄ "- 54 ¹ / ₃ " 2175 - 1237 - 1380
Crated dimensions (L-D-H)	inches mm	54 1/3"- 58 1/4"- 63 3/4" 1380-1480-1620	74"- 58 ¼"- 63 ¾" 1880-1480-1620	93 ¾"- 58 ¼"- 63 ¾" 2380-1480-1620	93 ¾"- 58 ¼"- 63 ¾" 2380-1480-1620
Refrigeration	Туре	Fan Ventilated	Fan Ventilated	Fan Ventilated	Fan Ventilated
Refrigerated display area	Туре	Deck / Shelves	Deck / Shelves	Deck / Shelves	Deck / Shelves
Operating temperature	°C / °F	+4 / 39.2	+4 / 39.2	+4 / 39.2	+4 / 39.2
Compressor	nr. / Type	1 / hermetic	1 / hermetic	1 / hermetic	1 / hermetic
Cooling power *	(W)	930	1160	1440	1100
Electric supply	(V/ph/Hz)	230/1/50 (UE) 120/1/60 (USA)	230/1/50 (UE) 120/1/60 (USA)	230/1/50 (UE) 120/1/60 (USA)	230/1/50 (UE) 120/1/60 (USA)
Power consumption	(W/A)	1000/5,8	1200/8,5	1600/9,0	1015/6,8
Defrost	Mode / type	electric	electric	electric	electric
Climatic class	N°/°C(F°)/H.R.	4+/35(95)/70%	4+/35(95)/70%	4+/35(95)/70%	4+/35(95)/70%
Refrigerant Gas	Туре	R452A	R452A	R452A	R452A
Net weight	Kg / Lb	266 / 586	350 / 771	430 / 992	330 / 727
Crated weight	Kg / Lb	391 / 862	525 / 1157	650 / 1433	575 / 1267



STANDARD FEATURE

- LED lighting system
- Front, top and side double glasses
- A.L.C airflow level control to manage the temperature on shelves (1 Only the display plate / 2 Extended on the first shelf / 3 Entire display volume)







OPTIONALS

- Self-rolling night curtain
- Condensate water tray with automatic evaporating
- S/s steps for display area
- Hot glass shelves with electric control
- Remote condensing unit
- Wheels kit





The company reserves the right to make modifications to the products without prior notice.

CIAM s.p.a. | Viale dei Pini 9 | 06081 | Petrignano di Assisi | PG - Italy | Tel: 0039 07580161 web: www.ciamweb.it | mail: info@ciamgroup.it







